MCM Neuss (GD2)

General Description: Fully coated White Lined Chipboard with grey back

Board Construction

TRIPLE PIGMENT COATING																		
-	7	7	7	7	7	7	7	DI	E-INKE	PIW	7	7	7	7	7	7	Ŧ	7
MECHANICAL PULP & SORTED PCW																		
								S	ORTED	PCW								
						٠.	٠.	PIC	GMENT	ATION			٠.			٠.	٠.	



Board Specification

Microns µm	Gsm	Stiffness /	Stiffness / Taber 15° bend mNm			
Tolerance (+/- 5%)	(+/- 2%)	MD (-15%)	CD (-15%)			
340	250	7.5	3.4	81%		
380	280	10.7	4.9	83%		
410	300	12.6	5.8	84%		
435	320	16.2	6.8	85%		
475	350	22.1	8.3	86%		
Tolerance (+/- 3%)						
520	380	25.7	10.3	87%		

What are the uses for this board?

Cartons:

Non-direct food contact, Direct Contact with Dry Foods, Household Goods, Garden Goods, Toys, DIY, Industrial, Electronics, Horticultural, Backing Boards and Stiffeners

Mill Certificates

- FSC
- ISO 9001
- PEFC
- ISEGA on request
- ISO 50001:2011

November 2020