



# Technical Data

ISO 9001 certified QMS  
FSC® certified product.

This grade is made with 56% recycled fibers and is guaranteed 100% recyclable (norm EN 13430).

Papers complying with the regulation CE N° 1935/2004 and may be used in direct contact with dry and non-fatty foodstuffs.

<b>Item designation</b>  <b>G 841</b>  Caliper (+/- 10% / ISO3034) : <b>0,90 mm</b> or <i>35,3 mil</i> Weight (+/- 7% /ISO536) : <b>432 g/m<sup>2</sup></b> or <i>88,5 lb/1000 ft<sup>2</sup></i>	<i>Cylinder thickness</i>		<i>Number of flutes/m</i>
	G	0,5	554

## Papers composition

Inner liner	Fluting 1	Centre liner 1	Fluting 2	Centre liner 2	Fluting 2	Outer liner
KBC180	CAN100					COB125

## Technical characteristics

Theoretical values

Tests	Burst(kPa)	Bulk (Cm3/g)
	<i>ISO 2759</i>	<i>ISO 3037</i>
Average	588	2,08
Min	558	1,87

Averages figures for 95% of the measured values. All tests are carried out under conditions of 23°C and 50% RH. ISO 187

All papers used are subject to strict quality controls.

Edited : 03/06/2020