

MCM Strong (GD2)(Venoplex)

General Description: Fully Coated White Lined Chipboard with a grey back

Board Construction

MULTIPLE PIGMENT COATING									
Printed PIW + Unprinted PIW									
Printed PIW + MECHANICAL PULP + PCW + Unprinted PIW									
PCW + Unprinted PIW									
PIGMENTATION									



Board Specification

Microns μm Tolerance (+/- 5%)	Gsm (+/- 2%)	Stiffness / Taber 15° bend mNm		Recycled %
		MD (-15%)	CD (-15%)	
410	280	13.3	5.5	> 75%
445	300	16.8	6.9	> 75%
490	325	21.1	8.6	> 75%
Tolerance (+/- 3%)				
530	350	25.4	10.3	> 75%
580	375	31.5	12.2	> 75%
620	400	37	14.6	> 75%
660	425	41.2	16.5	> 75%

What are the uses for this board?

Cartons:

Non-Direct Food Contact, Direct Contact with Dry Foods, Household Goods, Garden Goods, Toys, DIY, Industrial, Printed outers.

Mill Certificates

- FSC
- PEFC
- ISO 9001
- HACCP
- ISEGA on request
- ISO 14001 - 400gsm and above only
- EMAS - 400gsm and above only
- ISO 50001:2011 (max 550 μm)